


## Panelmonterade intag

Art.nr 1259




- skruvplintar
- med skyddslock

## Tekniska data

|                           |              |
|---------------------------|--------------|
| Ampere                    | 63 A         |
| Poler                     | 5 p          |
| Volt                      | 400 V        |
| Klockposition             | 6 h          |
| Hertz                     | 60-50 Hz     |
| Anslutningsteknologi      | skruvkontakt |
| Kontakt                   | standard     |
| Skyddstyp                 | IP67         |
| Vikt                      | 705 g        |
| Intyg om överensstämmelse | EAC, VDE     |

## Mått



| Drawing                              | Amp. | 16    |      |      | 32  |     |     | 63  |     |     |   |   |
|--------------------------------------|------|-------|------|------|-----|-----|-----|-----|-----|-----|---|---|
|                                      |      | Poles |      | 3    | 4   | 5   | 3   | 4   | 5   | 3   | 4 | 5 |
| 2 MB 62                              |      |       |      |      |     |     |     |     |     |     |   |   |
| Dim. in mm                           |      | a     | 85   | 85   | 85  | 85  | 85  | 108 | 108 | 108 |   |   |
|                                      |      | b     | 85   | 85   | 85  | 85  | 85  | 101 | 101 | 101 |   |   |
|                                      |      | c     | 132  | 132  | 131 | 131 | 137 | 164 | 164 | 164 |   |   |
|                                      |      | d     | 70   | 70   | 70  | 70  | 70  | 85  | 85  | 85  |   |   |
|                                      |      | e     | 70   | 70   | 70  | 70  | 70  | 77  | 77  | 77  |   |   |
|                                      |      | f     | 6.3  | 6.3  | 6.3 | 6.3 | 6.3 | 6.5 | 6.5 | 6.5 |   |   |
|                                      |      | g.    | 11   | 11   | 11  | 11  | 11  | 12  | 12  | 12  |   |   |
|                                      |      | g.1   | 2    | 2    | 2   | 2   | 2   | 2   | 2   | 2   |   |   |
|                                      |      | h     | 100  | 107  | 108 | 108 | 111 | 130 | 130 | 130 |   |   |
|                                      |      | s     | 70   | 87   | 94  | 94  | 102 | 114 | 114 | 114 |   |   |
|                                      |      | l     | 30   | 30   | 30  | 30  | 30  | 40  | 40  | 40  |   |   |
| Terminal for cond. cross             |      | 1     | 1    | 2,5  | 2,5 | 2,5 |     | 6   | 6   | 6   |   |   |
| section (mm <sup>2</sup> ) min.-max. |      |       | -2,5 | -2,5 | -6  | -6  | -6  | -16 | -16 | -16 |   |   |